

Tel. +49(0)911-642960

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.05.2023 Version number 6 (replaces version 5) Revision: 16.05.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

Marble Filler 1000 S T G · Trade name:

10503, 10505, 10506, 10507, 10512, 10515, 10536 · Article number:

GJA4-90C4-800T-DKM7 · UFI:

 1.2 Relevant identified uses of the substance or mixture and

No further relevant information available. uses advised against

· Application of the substance / the

Knife filler/ Surfacer mixture

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH

Fax. +49(0)911-644456 Lechstrasse 28 D 90451 Nürnberg e-mail info@akemi.de

· Further information obtainable

Laboratory 1.4 Emergency telephone

number: Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH

Tel. +49(0)911-64296-59

Reachable during the following office hours: Monday – Thursday from 07:30 a.m. to 16:30 p.m.

Friday from 07:30 a.m. to 13:30 p.m.

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

H226 Flammable liquid and vapour. Flam. Liq. 3

Skin Irrit. 2 H315 Causes skin irritation.

Eve Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Repr. 2 H361d Suspected of damaging the unborn child.

STOT RE 2 H373 May cause damage to the hearing organs through prolonged or repeated exposure.

Aguatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

Labelling according to Regulation

(EC) No 1272/2008

· Hazard pictograms

The product is classified and labelled according to the CLP regulation.







GHS07 GHS08 GHS02

· Signal word Warning

· Hazard-determining components of

labelling: styrene

maleic anhydride

Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and 2-[[2-(2-

hydroxyethoxy)ethyl](4-methylphenyl)amino]-ethanol

· Hazard statements H226 Flammable liquid and vapour.

H315 Causes skin irritation. H319 Causes serious eye irritation. H317 May cause an allergic skin reaction. H361d Suspected of damaging the unborn child.

(Contd. on page 2)



Page 2/15

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.05.2023 Version number 6 (replaces version 5) Revision: 16.05.2023

Trade name:	Marble	Filler	1000	S	Τ	G
-------------	--------	--------	------	---	---	---

(Contd. of page 1) H373 May cause damage to the hearing organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements P101 If medical advice is needed, have product container or label at

hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

P260 Do not breathe vapours.

P280 Wear protective gloves / eye protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated

clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue

rinsing.

P314 Get medical advice/attention if you feel unwell.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/

regional/national/international regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.∨P∨B: Not applicable.

· Determination of endocrine-

disrupting properties For information on endocrine disrupting properties see section 11.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 100-42-5 EINECS: 202-851-5 Index number: 601-026-00-0 Reg.nr.: 01-2119457861-32	styrene Flam. Liq. 3, H226 Repr. 2, H361d; STOT RE 1, H372; Asp. Tox. 1, H304 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 Aquatic Chronic 3, H412	<10%
CAS: 25013-15-4 EINECS: 246-562-2 Reg.nr.: 01-2119622074-50-0000	vinyltoluene Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Acute 1, H400; Aquatic Chronic 2, H411 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	1-5%
EC number: 911-490-9 Reg.nr.: 01-2119979579-10	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-ethanol Eye Dam. 1, H318 Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317 Aquatic Chronic 3, H412	<1%
CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5 Reg.nr.: 01-2119475103-46	ethyl acetate Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 EUH066	<1%

(Contd. on page 3)



Page 3/15

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.05.2023 Version number 6 (replaces version 5) Revision: 16.05.2023

Trade name: Marble Filler 1000 S T G

CAS: 108-31-6

(Contd. of page 2) maleic anhydride <1%

Resp. Sens. 1, H334; STOT RE 1, H372 EINECS: 203-571-6 Index number: 607-096-00-9 Skin Corr. 1B, H314; Eye Dam. 1, H318 Reg.nr.: 01-2119472428-31 Acute Tox. 4, H302; Skin Sens. 1A, H317

EUH071

Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.001 % Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

· General information: Take affected persons out into the fresh air.

Position and transport stably in side position.

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical

observation for at least 48 hours after the accident.

Supply fresh air. If required, provide artificial respiration. Keep patient warm. · After inhalation:

Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for

transportation.

· After skin contact: If skin irritation continues, consult a doctor.

Immediately wash with water and soap and rinse thoroughly.

Rinse opened eye for several minutes under running water. If symptoms persist, · After eye contact:

consult a doctor.

· After swallowing: A person vomiting while laying on their back should be turned onto their side.

4.2 Most important symptoms and effects, both acute and

delayed

Headache Dizziness Dizziness

Gastric or intestinal disorders

Nausea

Profuse sweating

Danger of impaired breathing. · Hazards

· 4.3 Indication of any immediate medical attention and special

treatment needed

If swallowed or in case of vomiting, danger of entering the lungs.

If swallowed, gastric irrigation with added, activated carbon.

SECTION 5: Firefighting measures

5.1 Extinguishing media

· Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol

resistant foam.

· For safety reasons unsuitable

extinguishing agents:

Water with full jet

5.2 Special hazards arising from

the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Carbon monoxide (CO)

Under certain fire conditions, traces of other toxic gases cannot be excluded.

5.3 Advice for firefighters

· Protective equipment: Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

Mount respiratory protective device.

(Contd. on page 4)



Page 4/15

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.05.2023 Version number 6 (replaces version 5) Revision: 16.05.2023

Trade name: Marble Filler 1000 S T G

(Contd. of page 3)

· Additional information Collect contaminated fire fighting water separately. It must not enter the sewage

system.

Dispose of fire debris and contaminated fire fighting water in accordance with

official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and

<u>emergency procedures</u> Ensure adequate ventilation

Keep away from ignition sources.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

• 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage

system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal

binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

• 6.4 Reference to other sections See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe

handling Keep receptacles tightly sealed.

Store in cool, dry place in tightly closed receptacles.

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and

<u>explosion protection:</u> Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by

<u>storerooms and receptacles:</u> Store only in the original receptacle.

Prevent any seepage into the ground.

· Information about storage in one

common storage facility:

Store away from foodstuffs.

· Further information about storage

conditions:

Store receptacle in a well ventilated area.

Keep container tightly sealed.

· Storage class:

• **7.3 Specific end use(s)** No further relevant information available.

(Contd. on page 5)



Page 5/15

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.05.2023 Version number 6 (replaces version 5) Revision: 16.05.2023

Trade name: Marble Filler 1000 S T G (Contd. of page 4) **SECTION 8: Exposure controls/personal protection** · 8.1 Control parameters · Ingredients with limit values that require monitoring at the workplace: 141-78-6 ethyl acetate IOELV Short-term value: 1468 mg/m³, 400 ppm Long-term value: 734 mg/m³, 200 ppm · DNELs 100-42-5 styrene Oral DNEL (Langzeit-wiederholt) 2.1 mg/kg bw/day (BEV) Dermal DNEL (Langzeit-wiederholt) 406 mg/kg bw/day (ARB) 343 mg/kg bw/day (BEV) Inhalative DNEL (Kurzzeit-akut) 289-306 mg/m³ Air (ARB) 174.25-182.75 mg/m³ Air (BEV) DNEL (Langzeit-wiederholt) 85 mg/m³ Air (ARB) 10.2 mg/m³ Air (BEV) 25013-15-4 vinyltoluene Oral DNEL (Langzeit-wiederholt) 0.0833 mg/kg bw/day (BEV) Dermal DNEL (Langzeit-wiederholt) 1.65 mg/kg bw/day (ARB) 0.595 mg/kg bw/day (BEV) Inhalative DNEL (Langzeit-wiederholt) 5.83 mg/m³ Air (ARB) 1.04 mg/m³ Air (BEV) Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl) amino]-ethanol Oral DNEL (Langzeit-wiederholt) 0.83 mg/kg bw/day (BEV) DNEL (Langzeit-wiederholt) 1.4 mg/kg bw/day (ARB) Dermal 0.83 mg/kg bw/day (BEV) Inhalative DNEL (Langzeit-wiederholt) 9.8 mg/m³ Air (ARB) 2.9 mg/m³ Air (BEV) 141-78-6 ethyl acetate Oral DNEL (Langzeit-wiederholt) 4.5 mg/kg bw/day (BEV) Dermal DNEL (Langzeit-wiederholt) 63 mg/kg bw/day (ARB) 37 mg/kg bw/day (BEV) Inhalative DNEL (Kurzzeit-akut) 1,468 mg/m³ Air (ARB) 734 mg/m³ Air (BEV) DNEL (Langzeit-wiederholt) 734 mg/m³ Air (ARB) 367 mg/m³ Air (BEV) 108-31-6 maleic anhydride DNEL (Langzeit-wiederholt) | 0.06 mg/kg bw/day (BEV) Oral Dermal DNEL (Kurzzeit-akut) 0.04 mg/kg bw/day (ARB) DNEL (Langzeit-wiederholt) 0.2 mg/kg bw/day (ARB) 0.1 mg/kg bw/day (BEV) Inhalative DNEL (Kurzzeit-akut) 0.2 mg/m³ Air (ARB) DNEL (Langzeit-wiederholt) 0.081 mg/m³ Air (ARB) 0.08 mg/m3 Air (BEV) (Contd. on page 6)

- EU



Page 6/15

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.05.2023 Version number 6 (replaces version 5) Revision: 16.05.2023

	(Contd. of non
PNECs	(Contd. of pag
100-42-5 styren	<u> </u>
PNEC (wässrig)	
T NEO (Wassing)	0.014 mg/l (MW)
	0.028 mg/l (SW)
	0.04 mg/l (WAS)
PNEC (fest)	0.2 mg/kg Trockengew (BO)
FINEC (lest)	
	0.307 mg/kg Trockengew (MWS)
05040 45 4!	0.614 mg/kg Trockengew (SWS)
25013-15-4 viny	
PNEC (wässrig)	
	0.000319 mg/l (MW)
DNEO (6 1)	0.0000319 mg/l (SW)
PNEC (fest)	0.00471 mg/kg Trockengew (BO)
	0.025 mg/kg Trockengew (MWS)
	1.245 mg/kg Trockengew (SWS)
Reaction mass amino]-ethanol	of 2,2'-[(4-methylphenyl)imino]bisethanol and 2-[[2-(2-hydroxyethoxy)ethyl](4-methylpheny
PNEC (wässrig)	10 mg/l (KA)
	0.005 mg/l (MW)
	0.048 mg/l (SW)
PNEC (fest)	0.21 mg/kg Trockengew (BO)
	0.12 mg/kg Trockengew (MWS)
	1.2 mg/kg Trockengew (SWS)
141-78-6 ethyl a	
PNEC (wässrig)	
ζ,	0.024 mg/l (MW)
	0.24 mg/l (SW)
	1.65 mg/l (WAS)
PNEC (fest)	0.148 mg/kg Trockengew (BO)
- ()	0.115 mg/kg Trockengew (MWS)
	1.15 mg/kg Trockengew (SWS)
108-31-6 maleic	
PNEC (wässrig)	
· ···=o (wassing)	0.0038 mg/l (MW)
	0.038 mg/l (SW)
	0.4281 mg/l (WAS)
PNEC (fest)	0.037 mg/kg Trockengew (BO)
T NEO (163t)	0.0296 mg/kg Trockengew (MWS)
	0.296 mg/kg Trockengew (SWS)
	0.290 mg/kg mockengew (SWS)

8.2 Exposure controls

- · Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment

· General protective and hygienic

measures: Do not eat, drink, smoke or sniff while working.

(Contd. on page 7)



Page 7/15

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.05.2023 Version number 6 (replaces version 5) Revision: 16.05.2023

Trade name: Marble Filler 1000 S T G

· Hand protection

(Contd. of page 6)

Use skin protection cream for skin protection. Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin.

Short term filter device: · Respiratory protection:

Filter A/P2

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. Preventive skin protection by use of skin-protecting agents is recommended.

After use of gloves apply skin-cleaning agents and skin cosmetics.

Skin protection agent recommendation for preventive skin shelter without use of protective gloves:

ARRETIL (http://www.stoko.com)

Skin protection agent recommendation for preventive skin shelter in application and combination of protective gloves:

STOKO EMULSION (http://www.stoko.com)

Skin protection recommendation for skin cleaning after product handling:

SOLOPOL (http://www.stoko.com) Kresto Classic (http://debstoko.com)

Skin protection agent recommendation for skin aftercare:

STOKO VITAN (http://www.stoko.com)

The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory anylyses of the company KCL GmbH in compliance with EN374.

This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: http://www.kcl.de).



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves Butyl rubber, BR

> The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

Value for the permeation: Level ≤ 1 , 30 min

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact gloves made of the following materials are suitable:

Butyl rubber, BR

(Contd. on page 8)



Page 8/15

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.05.2023 Version number 6 (replaces version 5) Revision: 16.05.2023

Trade name: Marble Filler 1000 S T G

Butoject (KCL, Art_No. 897, 898)

(Contd. of page 7)

· As protection from splashes gloves made of the following materials are

suitable:

Butyl rubber, BR

Butoject (KCL, Art_No. 897, 898)

Not suitable are gloves made of

the following materials:

Fluorocarbon rubber (Viton)

Nitrile rubber, NBR Chloroprene rubber, CR

Leather gloves Strong material gloves Natural rubber, NR

Eye/face protection



Tightly sealed goggles

· <u>Body protection:</u> Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

· General Information

· Colour: Different according to colouring

· Odour: Characteristic
· Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling range 145 °C

· Lower and upper explosion limit

 · Lower:
 1.2 Vol %

 · Upper:
 8.9 Vol %

 · Flash point:
 32 °C

 · Auto-ignition temperature:
 480 °C

Not determined.

Not applicable

· Viscosity:

· <u>Kinematic viscosity</u> Not determined.

Not applicable Not determined. Not applicable

Solubility

Dynamic:

· <u>water:</u> Not miscible or difficult to mix.

· <u>Vapour pressure at 20 °C:</u> 6 hPa

Density and/or relative density

Density at 20 °C: 1.74 g/cm³ ([1,69 - 1,80 g/cm³])

9.2 Other information

· <u>Appearance:</u>

· <u>Form:</u> Pasty

· Important information on protection of health and

environment, and on safety.

· <u>Ignition temperature:</u> Product is not selfigniting.

Explosive properties: Product is not explosive. However, formation of explosive air/

vapour mixtures are possible.

· Solvent content:

· Organic solvents: 13.4 % · Solids content: 84.5 %

· Information with regard to physical hazard classes

· <u>Explosives</u> Void

(Contd. on page 9)



Page 9/15

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.05.2023 Version number 6 (replaces version 5) Revision: 16.05.2023

Trade name: Marble Filler 1000 S T G

(Contd. of page 8)

· Flammable gases	Void
Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void

· Flammable liquids Flammable liquid and vapour.

Flammable solids · Self-reactive substances and mixtures Void · Pyrophoric liquids Void Pyrophoric solids Void · Self-heating substances and mixtures Void

· Substances and mixtures, which emit flammable

gases in contact with water

Void · Oxidising liquids Void Void Oxidising solids Organic peroxides Void · Corrosive to metals Void · Desensitised explosives Void

SECTION 10: Stability and reactivity

No further relevant information available. · 10.1 Reactivity

10.2 Chemical stability · Thermal decomposition /

conditions to be avoided: No decomposition if used and stored according to specifications.

10.3 Possibility of hazardous

reactions

Exothermic polymerisation. Reacts with peroxides and other radical forming substances.

Reacts with acids, alkalis and oxidising agents.

· 10.4 Conditions to avoid No further relevant information available. No further relevant information available · 10.5 Incompatible materials:

10.6 Hazardous decomposition

products: Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx) Possible in traces.

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Based on available data, the classification criteria are not met. · Acute toxicity

· LD/LC50 values relevant for classification: **ATE (Acute Toxicity Estimates)** Inhalative LC50/4 h 86.9 mg/l

100-42-5	100-42-5 styrene		
Oral	LD50	>2,000 mg/kg (rat)	
Dermal	LD50	>2,000 mg/kg (rat) (OECD-Prüfrichtlinie 402)	
Inhalative	LC50/4h	9.5 mg/m3 (mouse)	
		11,800 mg/m3 (rat)	
	LC50/4 h	11.8 mg/l (rat)	
	NOAEC	4.34 mg/l (rat)	

(Contd. on page 10)



Page 10/15

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.05.2023 Version number 6 (replaces version 5) Revision: 16.05.2023

Trade	name:	Marble	Filler	1000	S T	G

25042.45	4 minultalus - s	(Contd. of page
	4 vinyltoluene	
Oral	LD50	3,375 mg/kg (rat)
	NOAEL	600 mg/kg (rat)
Dermal	LD50	4,585 mg/kg (rabbit)
Inhalative	LC50/4h	>16,891 mg/m3 (rat)
	LC50/4 h	11 mg/l (ATE)
Reaction amino]-et		4-methylphenyl)imino]bisethanol and 2-[[2-(2-hydroxyethoxy)ethyl](4-methylpheny
Oral	LD50	619 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
141-78-6	ethyl acetate	
Oral	LD50	4,100 mg/kg (mouse)
		5,620 mg/kg (rat)
		4,934 mg/kg (rbt) (OECD 401)
	NOAEL-Werte	900 mg/kg (rat)
Dermal	LD50	>18,000 mg/kg (rabbit)
Inhalative	LC50	58 mg/l (rat)
	LC50/4 h	1,600 mg/l (rat)
	LC50/1h	200 mg/l (rat)
	LC50/8h	5.86 mg/l (rat)
	LC50/48h	333 mg/l (Leuciscus idus)
108-31-6 ו	maleic anhydrid	
Oral	LD50	1,090-2,620 mg/kg (rabbit)
		400-480 mg/kg (rat)
Dermal	LD50	2,620 mg/kg (rabbit)
Inhalative	LC50/1h	>4.35 mg/l (rat)
	LC50/48h	138 mg/l (lem)
Skin corro	sion/irritation	Causes skin irritation.
	∕e damage/irrita	
	y or skin sensiti	
	mutagenicity	Based on available data, the classification criteria are not met.
Carcinoge		Based on available data, the classification criteria are not met.
	tive toxicity gle exposure	Suspected of damaging the unborn child. Based on available data, the classification criteria are not met.
2101-9110	ar exhosning	Dased on available data, the classification chileria are not filet.

· 11.2 Information on other hazards

· Endocrine disrupting properties

· STOT-repeated exposure

· Aspiration hazard

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

Aquatic toxicity:

100-42-5 styrene

EC50/96h | 6.3 mg/l (Pseudokirchneriella subcapitata)

exposure.

May cause damage to the hearing organs through prolonged or repeated

Based on available data, the classification criteria are not met.

(Contd. on page 11)



Page 11/15

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.05.2023 Version number 6 (replaces version 5) Revision: 16.05.2023

ade name: Ma	arble Filler 1000 S T G
	(Contd. of page
EC50	500 mg/l (BES) (ISO Vorschrift 8192-1986 E)
	5.5 mg/l (Photobac. phosphoreum)
IC50/72h	4.9 mg/l (green alge)
	1.4 mg/l (selenastrum capricornutum)
IC5/8d	>200 mg/l (Scenedesmus quadricauda)
EC10/16h	72 mg/l (pseudomonas putida)
EC50/16h	>72 mg/l (pseudomonas putida)
EC50/8d	>200 mg/l (Scenedesmus quadricauda)
EC50/72u	>1-<10 mg/l (green alge)
EC20/0.5h	140 mg/l (BES) (OECD 209)
NOEC/21d	1.01 mg/l (daphnia magna)
EC10	0.28 mg/l (Pseudokirchneriella subcapitata) (EPA OTS 797.1050)
EC50/48h	0.56 mg/l (green alge)
	3.3-7.4 mg/l (daphnia magna)
EC50/72h	0.46-4.3 mg/l (Pseudokirchneriella subcapitata)
LC50/96h	>1-<10 mg/l (piscis)
	19.03-33.53 mg/l (lem)
	3.24-4.99 mg/l (pimephales promelas)
	6.75-14.5 mg/l (Pimephales promelas)
	58.75-95.32 mg/l (poecilia reticulata)
LC50/72h	4.9 mg/l (green alge)
25013-15-4 v	
	2.6 mg/l (Bluegill.)
EC50/48h	9.3 mg/l (daphnia magna)
	4.3 mg/l (Pseudokirchneriella subcapitata)
NOEC	0.563 mg/l (piscis)
	1.6 mg/l (green alge)
NOEC/21d	0.32 mg/l (daphnia magna)
	0.563 mg/l (piscis)
EC10	0.25 mg/l (Desmodesmus subspicatus)
EC50/72h	0.319 mg/l (Desmodesmus subspicatus)
	5.2 mg/l (Fathead minnow)
	2.6 mg/l (selenastrum capricornutum)
LC50/96h	5.2-23.4 mg/l (piscis)
	5.2 mg/l (pimephales promelas)
Reaction ma amino]-etha	ass of 2,2'-[(4-methylphenyl)imino]bisethanol and 2-[[2-(2-hydroxyethoxy)ethyl](4-methylpheny nol
EC50/48h	48 mg/l (daphnia magna)
EC50/72h	>100 mg/l (Pseudokirchneriella subcapitata)
LC50/96h	>100 mg/l (Cyprinus carpio)
141-78-6 eth	yl acetate
EC50/96h	220 mg/l (Pimephales promelas)
EC10/18h	2,900 mg/l (pseudomonas putida)
EC50/48h	610 mg/l (daphnia magna) (DIN 38412)
-	5,600 mg/l (Desmodesmus subspicatus)
	(Contd. on page



Page 12/15

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.05.2023 Version number 6 (replaces version 5) Revision: 16.05.2023

Trade name:	Marble	Filler	1000	S T	G
-------------	--------	--------	------	-----	---

		(Contd. of page 11)
CEU/10P	2 200 mg/l (Coopedcomus subopicatus)	

1000	74011	0,000 mg/r (Occircucarinus subspicatus)
LC 0		29.3 mg/l (rat)
NOE	LR/72h	>100 mg/l (Desmodesmus subspicatus)

NOEC/21d 2.4 mg/l (daphnia magna)

EC10 2,900 mg/l (pseudomonas putida) EC50/48h 3,300 mg/l (Scenedesmus subspicatus) LC50/96h 230 mg/l (Oncorhynchus mykiss) 230 mg/l (Pimephales promelas)

108-31-6 maleic anhydride

	316-330 mg/l (daphnia magna)
	77 mg/l (daphnia magna)
	44.6 mg/l (pseudomonas putida)
	42.81 mg/l (daphnia magna)
ErC50/72h	74.35 mg/l (Pseudokirchneriella s

subcapitata) (OECD 202)

NOELR/72h 150 mg/l (Pseudokirchneriella subcapitata)

NOEC/21d 10 mg/l (daphnia magna)

EC50/72h 29 mg/l (Desmodesmus subspicatus)

> 74.32 mg/l (Pseudokirchneriella subcapitata) >150 mg/l (Selenastrum capricornutum)

LC50/96h 75 mg/l (lepomis macrochirus)

75 mg/l (Oncorhynchus mykiss)

12.2 Persistence and

degradability No further relevant information available. 12.3 Bioaccumulative potential No further relevant information available. · 12.4 Mobility in soil No further relevant information available.

· 12.5 Results of PBT and vPvB assessment

· PBT: Not applicable. · vPvB: Not applicable.

· 12.6 Endocrine disrupting

properties The product does not contain substances with endocrine disrupting properties.

· 12.7 Other adverse effects

· Additional ecological information:

· General notes: Do not allow product to reach ground water, water course or sewage system.

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

Must not be disposed together with household garbage. Do not allow product to · Recommendation reach sewage system.

	· European	waste catalogue
		MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS
	20 01 00	separately collected fractions (except 15 01)
Ī	20 01 27*	paint, inks, adhesives and resins containing hazardous substances

Uncleaned packaging:

· Recommendation: Empty contaminated packagings thoroughly. They may be recycled after

thorough and proper cleaning.

(Contd. on page 13)



Page 13/15

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.05.2023 Version number 6 (replaces version 5) Revision: 16.05.2023

Trade name: Marble Filler 1000 S T G

(Contd. of page 12)

SECTION 14: Transport information

Recommended cleansing agents: Alcohol

· 14.1 UN number or ID number · ADR, IMDG, IATA UN3269

14.2 UN proper shipping name

· ADR 3269 POLYESTER RESIN KIT POLYESTER RESIN KIT

· 14.3 Transport hazard class(es)

· ADR



· <u>Class</u> 3 (FT3) Flammable liquids.

· <u>Label</u> 3

· IMDG, IATA



· Class 3 Flammable liquids. · Label 3

<u>abei</u>

14.4 Packing group

· <u>ADR, IMDG, IATA</u> III

· 14.5 Environmental hazards:

· Marine pollutant:

• 14.6 Special precautions for user Warning: Flammable liquids.

· Hazard identification number (Kemler code):

· EMS Number: F-E,S-D
· Stowage Category A

· 14.7 Maritime transport in bulk according to IMO

instruments Not applicable.

· Transport/Additional information:

· ADR

Limited quantities (LQ)
 Excepted quantities (EQ)
 5L
 Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

Transport categoryTunnel restriction codeD/E

Remarks: Without hardener component: no dangerous goods < 450 l

· IMDG

· Limited quantities (LQ) 5L

· Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 14)



Page 14/15

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.05.2023 Version number 6 (replaces version 5) Revision: 16.05.2023

Trade name: Marble Filler 1000 S T G

(Contd. of page 13)

• <u>Remarks:</u> Without hardener component: no dangerous goods < 30 I

·IATA

· Remarks: Without hardener component: 3/III UN 1866 Resin Solution

· UN "Model Regulation": UN 3269 POLYESTER RESIN KIT, 3, III

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances -

ANNEX I

None of the ingredients is listed.

Seveso category

P5c FLAMMABLE LIQUIDS

· Qualifying quantity (tonnes) for the application of lower-tier

requirements 5,000 t

· Qualifying quantity (tonnes) for the

application of upper-tier

requirements 50,000 t

· REGULATION (EC) No 1907/2006

ANNEX XVII Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· National regulations:

· Information about limitation of use: Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be

observed.

· Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

· Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· VOC EU 233.1 g/l

15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

(Contd. on page 15)



AKEMI®

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.05.2023 Version number 6 (replaces version 5) Revision: 16.05.2023

Trade name: Marble Filler 1000 S T G

(Contd. of page 14)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheets is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

 Department issuing SDS: Laboratory · Date of previous version: 03.06.2022

· Version number of previous version:

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European

Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1B: Skin corrosion/irritation - Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Resp. Sens. 1: Respiratory sensitisation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1 Skin Sens. 1A: Skin sensitisation - Category 1A

Repr. 2: Reproductive toxicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3