

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 23.08.2023

Version number 3 (replaces version 2)

Revision: 23.08.2023

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name: **Stone Sealer - satin finish**

Article number: 10838, 10839, 10854

UFI: 2M92-90E4-S002-HCFX

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Sealing

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH  
Lechstrasse 28  
D 90451 Nürnberg

Tel. +49(0)911-642960  
Fax. +49(0)911-644456  
e-mail info@akemi.de

Further information obtainable from:

Laboratory

#### 1.4 Emergency telephone number:

Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH  
Tel. +49(0)911-64296-59  
Reachable during the following office hours:  
Monday – Thursday from 07:30 a.m. to 16:30 p.m.  
Friday from 07:30 a.m. to 13:30 p.m.

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

Hazard pictograms

The product is classified and labelled according to the CLP regulation.



GHS02 GHS07 GHS08 GHS09

Signal word

Danger

Hazard-determining components of labelling:

Hazard statements

Solvent naphtha (petroleum), light arom.

H226 Flammable liquid and vapour.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P101

If medical advice is needed, have product container or label at hand.

P102

Keep out of reach of children.

P103

Read carefully and follow all instructions.

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261

Avoid breathing vapours.

P271

Use only outdoors or in a well-ventilated area.

(Contd. on page 2)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.08.2023

Version number 3 (replaces version 2)

Revision: 23.08.2023

**Trade name: Stone Sealer - satin finish**

(Contd. of page 1)

P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P304+P312	IF INHALED: Call a POISON CENTER/doctor if you feel unwell.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information: EUH066 Repeated exposure may cause skin dryness or cracking. Contains methyl methacrylate, n-butyl methacrylate. May produce an allergic reaction.

**· 2.3 Other hazards**· Results of PBT and vPvB assessment· PBT: Not applicable.· vPvB: Not applicable.· Determination of endocrine-disrupting properties

For information on endocrine disrupting properties see section 11.

**SECTION 3: Composition/information on ingredients****· 3.2 Mixtures**· Description: Mixture of substances listed below with nonhazardous additions.· Dangerous components:

CAS: 64742-95-6 EC number: 918-668-5 Index number: 649-356-00-4 Reg.nr.: 01-2119455851-35	Solvent naphtha (petroleum), light arom. Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H335-H336 EUH066	50-100%
CAS: 80-62-6 EINECS: 201-297-1 Index number: 607-035-00-6 Reg.nr.: 01-2119452498-28	methyl methacrylate Flam. Liq. 2, H225 Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	<1%
CAS: 97-88-1 EINECS: 202-615-1 Index number: 607-033-00-5 Reg.nr.: 01-2119486394-28-xxxx	n-butyl methacrylate Flam. Liq. 3, H226 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	<1%

· Additional information: For the wording of the listed hazard phrases refer to section 16.**SECTION 4: First aid measures****· 4.1 Description of first aid measures**

· General information: Immediately remove any clothing soiled by the product. Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Take affected persons out into the fresh air.  
Position and transport stably in side position.

· After inhalation: Supply fresh air; consult doctor in case of complaints.  
In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 3)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 23.08.2023

Version number 3 (replaces version 2)

Revision: 23.08.2023

**Trade name: Stone Sealer - satin finish**

(Contd. of page 2)

- After skin contact: Immediately wash with water and soap and rinse thoroughly.  
If skin irritation continues, consult a doctor.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Do not induce vomiting; call for medical help immediately.
- **4.2 Most important symptoms and effects, both acute and delayed**
  - Breathing difficulty
  - Headache
  - Dizziness
  - Dizziness
  - Nausea
- Hazards Danger of impaired breathing.
- **4.3 Indication of any immediate medical attention and special treatment needed**
  - If swallowed, gastric irrigation with added, activated carbon.

**SECTION 5: Firefighting measures**

- **5.1 Extinguishing media**
- Suitable extinguishing agents: CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
  - Formation of toxic gases is possible during heating or in case of fire.
  - In case of fire, the following can be released:
  - Carbon monoxide (CO)
  - Under certain fire conditions, traces of other toxic gases cannot be excluded.
- **5.3 Advice for firefighters**
- Protective equipment:
  - Do not inhale explosion gases or combustion gases.
  - Wear fully protective suit.
  - Wear self-contained respiratory protective device.

**SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures**
  - Wear protective equipment. Keep unprotected persons away.
  - Ensure adequate ventilation
  - Keep away from ignition sources.
  - Use respiratory protective device against the effects of fumes/dust/aerosol.
- **6.2 Environmental precautions:**
  - Inform respective authorities in case of seepage into water course or sewage system.
  - Do not allow product to reach sewage system or any water course.
  - Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
  - Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
  - Ensure adequate ventilation.
  - Dispose of the material collected according to regulations.
- **6.4 Reference to other sections**
  - See Section 7 for information on safe handling.
  - See Section 8 for information on personal protection equipment.
  - See Section 13 for disposal information.

(Contd. on page 4)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.08.2023

Version number 3 (replaces version 2)

Revision: 23.08.2023

**Trade name: Stone Sealer - satin finish**

(Contd. of page 3)

**SECTION 7: Handling and storage****7.1 Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.  
 Keep receptacles tightly sealed.  
 Store in cool, dry place in tightly closed receptacles.  
 Keep away from heat and direct sunlight.  
 Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).  
 Use only in well ventilated areas.

**Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.  
 Protect against electrostatic charges.  
 Protect from heat.  
 Highly volatile, flammable constituents are released during processing.

**7.2 Conditions for safe storage, including any incompatibilities****Storage:****Requirements to be met by storerooms and receptacles:**

Store in a cool location.  
 Store only in the original receptacle.  
 Prevent any seepage into the ground.

**Information about storage in one common storage facility:**

Store away from oxidising agents.  
 Store away from foodstuffs.

**Further information about storage conditions:**

Store in cool, dry conditions in well sealed receptacles.  
 Keep container tightly sealed.  
 Protect from heat and direct sunlight.  
 Store receptacle in a well ventilated area.

**Storage class:**

3

**7.3 Specific end use(s)**

No further relevant information available.

**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Ingredients with limit values that require monitoring at the workplace:****64742-95-6 Solvent naphtha (petroleum), light arom.**OEL | Long-term value: 100 mg/m<sup>3</sup>, 20 ppm**80-62-6 methyl methacrylate**IOELV | Short-term value: 100 ppm  
Long-term value: 50 ppm**DNELs****64742-95-6 Solvent naphtha (petroleum), light arom.**

Oral	DNEL (Langzeit-wiederholt)	11 mg/kg bw/day (BEV)
Dermal	DNEL ( Langzeit-wiederholt)	25 mg/kg bw/day (ARB)
		11 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	150 mg/m <sup>3</sup> Air (ARB)
		32 mg/m <sup>3</sup> Air (BEV)

**80-62-6 methyl methacrylate**

Oral	DNEL (Kurzzeit-akut)	0.25 mg/kg bw/day (BEV)
Dermal	DNEL (Kurzzeit-akut)	1.5 mg/kg bw/day (ARB)

(Contd. on page 5)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.08.2023

Version number 3 (replaces version 2)

Revision: 23.08.2023

**Trade name: Stone Sealer - satin finish**

(Contd. of page 4)

Inhalative	DNEL ( Langzeit-wiederholt)	1.5 mg/kg bw/day (BEV) 1.5-13.67 mg/kg bw/day (ARB)
	DNEL (Kurzzeit-akut)	1.5-8.2 mg/kg bw/day (BEV) 29.6-416 mg/m <sup>3</sup> Air (ARB)
	DNEL (Langzeit-wiederholt)	6.3-104 mg/m <sup>3</sup> Air (BEV) 208 mg/m <sup>3</sup> Air (ARB)
		74.3-104 mg/m <sup>3</sup> Air (BEV)

**97-88-1 n-butyl methacrylate**

Dermal	DNEL ( Langzeit-wiederholt)	5 mg/kg bw/day (ARB)
Inhalative	DNEL (Langzeit-wiederholt)	409 mg/m <sup>3</sup> Air (ARB)

## · PNECs

**80-62-6 methyl methacrylate**

PNEC (wässrig)	10 mg/l (KA)
	0.094 mg/l (MW)
	0.94 mg/l (SW)
	0.15-0.94 mg/l (WAS)
PNEC (fest)	1.47 mg/kg Trockengew (BO)
	0.102 mg/kg Trockengew (MWS)
	10.2 mg/kg Trockengew (SWS)

**97-88-1 n-butyl methacrylate**

PNEC (wässrig)	0.17 mg/l (SW)
----------------	----------------

· Additional information: The lists valid during the making were used as basis.· **8.2 Exposure controls**

- Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Do not inhale gases / fumes / aerosols.

Do not eat, drink, smoke or sniff while working.

Use skin protection cream for skin protection.

Clean skin thoroughly immediately after handling the product.

- Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. Use suitable respiratory protective device in case of insufficient ventilation.

Filter AX

- Hand protection Preventive skin protection by use of skin-protecting agents is recommended.

After use of gloves apply skin-cleaning agents and skin cosmetics.

Skin protection agent recommendation for preventive skin shelter without use of protective gloves:

STOKODERM (<http://www.stoko.com>)

Skin protection agent recommendation for preventive skin shelter in application and combination of protective gloves:

STOKO EMULSION (<http://www.stoko.com>)

Skin protection recommendation for skin cleaning after product handling:

FRAPANTOL (<http://www.stoko.com>)

Skin protection agent recommendation for skin aftercare:

(Contd. on page 6)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.08.2023

Version number 3 (replaces version 2)

Revision: 23.08.2023

**Trade name: Stone Sealer - satin finish**

(Contd. of page 5)

STOKO VITAN (<http://www.stoko.com>)

The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory analyses of the company KCL GmbH in compliance with EN374.

This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: <http://www.kcl.de>).

**Protective gloves**

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

Fluorocarbon rubber (Viton)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Value for the permeation: Level  $\leq$  6, 480 min

· For the permanent contact gloves made of the following materials are suitable:

Fluorocarbon rubber (Viton)

Vitoject (KCL, Art\_No. 890)

· As protection from splashes gloves made of the following materials are suitable:

Fluorocarbon rubber (Viton)

Vitoject (KCL, Art\_No. 890)

Nitrile rubber, NBR

Camatril (KCL, 730, 731, 732, 733)

· Not suitable are gloves made of the following materials:

Natural rubber, NR

Chloroprene rubber, CR

Butyl rubber, BR

· Eye/face protection

Safety glasses

· Body protection:

Protective work clothing

**SECTION 9: Physical and chemical properties**· **9.1 Information on basic physical and chemical properties**· General Information· Colour:

Colourless

· Odour:

Characteristic

· Melting point/freezing point:

Undetermined.

· Boiling point or initial boiling point and boiling range

162 °C

· Lower and upper explosion limit· Lower:

0.8 Vol %

· Upper:

7 Vol %

· Flash point:

39 °C

(Contd. on page 7)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.08.2023

Version number 3 (replaces version 2)

Revision: 23.08.2023

**Trade name: Stone Sealer - satin finish**

(Contd. of page 6)

· <u>Auto-ignition temperature:</u>	450 °C
· <u>pH</u>	Not determined. Not applicable
· <u>Viscosity:</u>	
· <u>Kinematic viscosity at 20 °C</u>	15 s (DIN 53211/4)
· <u>Dynamic:</u>	Not determined.
· <u>Solubility</u>	
· <u>water:</u>	Not miscible or difficult to mix.
· <u>Vapour pressure at 20 °C:</u>	5 hPa
· <u>Density and/or relative density</u>	
· <u>Density at 20 °C:</u>	0.9 g/cm <sup>3</sup>

**· 9.2 Other information**

· <u>Appearance:</u>	
· <u>Form:</u>	Fluid
· <u>Important information on protection of health and environment, and on safety.</u>	
· <u>Ignition temperature:</u>	Product is not selfigniting.
· <u>Explosive properties:</u>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· <u>Solvent content:</u>	
· <u>Organic solvents:</u>	80.4 %

· <u>Information with regard to physical hazard classes</u>	
· <u>Explosives</u>	Void
· <u>Flammable gases</u>	Void
· <u>Aerosols</u>	Void
· <u>Oxidising gases</u>	Void
· <u>Gases under pressure</u>	Void
· <u>Flammable liquids</u>	Flammable liquid and vapour.
· <u>Flammable solids</u>	Void
· <u>Self-reactive substances and mixtures</u>	Void
· <u>Pyrophoric liquids</u>	Void
· <u>Pyrophoric solids</u>	Void
· <u>Self-heating substances and mixtures</u>	Void
· <u>Substances and mixtures, which emit flammable gases in contact with water</u>	Void
· <u>Oxidising liquids</u>	Void
· <u>Oxidising solids</u>	Void
· <u>Organic peroxides</u>	Void
· <u>Corrosive to metals</u>	Void
· <u>Desensitised explosives</u>	Void

**SECTION 10: Stability and reactivity**

· <b>10.1 Reactivity</b>	No further relevant information available.
· <b>10.2 Chemical stability</b>	
· <u>Thermal decomposition / conditions to be avoided:</u>	No decomposition if used according to specifications. No decomposition if used and stored according to specifications.
· <b>10.3 Possibility of hazardous reactions</b>	Reacts with strong oxidising agents.
· <b>10.4 Conditions to avoid</b>	No further relevant information available.
· <b>10.5 Incompatible materials:</b>	No further relevant information available.
· <b>10.6 Hazardous decomposition products:</b>	Flammable gases/vapours

(Contd. on page 8)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.08.2023

Version number 3 (replaces version 2)

Revision: 23.08.2023

**Trade name: Stone Sealer - satin finish**

Carbon monoxide and carbon dioxide

(Contd. of page 7)

**SECTION 11: Toxicological information****11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

**64742-95-6 Solvent naphtha (petroleum), light arom.**

Oral	LD50	3,592 mg/kg (rat)
Dermal	LD50	>3,160 mg/kg (rabbit) >2,000 mg/kg (rat)

**80-62-6 methyl methacrylate**

Oral	LD50	7,872 mg/kg (rat) (OECD 401)
	NOAEL	2,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4h	4,632 mg/m <sup>3</sup> (rat)
	LC50/4 h	29.8 mg/l (rat)
	NOAEL	25 mg/m <sup>3</sup> (rat)

**97-88-1 n-butyl methacrylate**

Oral	LD50	>2,000 mg/kg (rat) (OECD 401)
	NOAEL	120 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit) (OECD 402)
Inhalative	LC50/4 h	29 mg/l (rat) (OECD 403)

- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure May cause respiratory irritation. May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard May be fatal if swallowed and enters airways.

**11.2 Information on other hazards**

· Endocrine disrupting properties

None of the ingredients is listed.

**SECTION 12: Ecological information****12.1 Toxicity**

· Aquatic toxicity:

**64742-95-6 Solvent naphtha (petroleum), light arom.**

EC50	<10 mg/l (daphnia magna)
IC50	<10 mg/l (daphnia magna)
LC50	<10 mg/l (algae)
	>1-<10 mg/l (piscis)
EL50/48h	3.2 mg/l (ceriodaphnia Dubai)
	3.2 mg/l (daphnia magna)
EL50/72h	2.6-2.9 mg/l (Pseudokirchneriella subcapitata)

(Contd. on page 9)



## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 23.08.2023

Version number 3 (replaces version 2)

Revision: 23.08.2023

**Trade name: Stone Sealer - satin finish**

(Contd. of page 8)

LL50/96h	2.9 mg/l (Selenastrum capricornutum)
NOELR/72h	9.2 mg/l (Oncorhynchus mykiss)
NOELR/72h	1 mg/l (Pseudokirchneriella subcapitata)
EC50/48h	3.2 mg/l (daphnia magna)
EC50/72h	2.9 mg/l (Pseudokirchneriella subcapitata)
LC50/96h	9.2 mg/l (Oncorhynchus mykiss)

**80-62-6 methyl methacrylate**

EC50/96h	170 mg/l (Pseudokirchneriella subcapitata)
EC50/48h	69 mg/l (daphnia magna) (OECD 202)
EC0	100 mg/l (pseudomonas putida)
NOEC	9.4 mg/kg (Danio rerio.) (OECD 210)
NOEC	>100 mg/l (Selenastrum capricornutum)
NOEC/21d	37 mg/l (daphnia magna) (OECD 202)
EC50/72h	>110 mg/l (Selenastrum capricornutum)
LC50/96h	153.9-341.8 mg/l (lem)
	>79 mg/l (Oncorhynchus mykiss) (OECD 203)
	125-275 mg/l (pimephales promelas)
	326.4-426.9 mg/l (poecilia reticulata)

**97-88-1 n-butyl methacrylate**

EC50/96h	130 mg/l (Pseudokirchneriella subcapitata)
EC50	253.6 mg/l (pseudomonas putida) (lit.)
IC50/72h	31.2 mg/l (Selenastrum capricornutum) (OECD 201)
EC50/48h	32 mg/l (daphnia magna)
NOELR/72h	24.8 mg/l (Pseudokirchneriella subcapitata)
NOEC/21d	1.1 mg/l (daphnia magna)
EC50/48h	25.4 mg/l (daphnia magna) (OECD 202)
LC50/96h	11 mg/l (piscis)
	5.57 mg/l (Oryzias latipes) (OECD 203)
	11 mg/l (pimephales promelas)

- **12.2 Persistence and degradability**

No further relevant information available.

- **12.3 Bioaccumulative potential**

No further relevant information available.

- **12.4 Mobility in soil**

No further relevant information available.

- **12.5 Results of PBT and vPvB assessment**

- **PBT:**

Not applicable.

- **vPvB:**

Not applicable.

- **12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

- **12.7 Other adverse effects**

- **Remark:**

Toxic for fish

- **Additional ecological information:**

- **General notes:**

Do not allow product to reach ground water, water course or sewage system.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

(Contd. on page 10)

EU

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.08.2023

Version number 3 (replaces version 2)

Revision: 23.08.2023

**Trade name: Stone Sealer - satin finish**

(Contd. of page 9)

**SECTION 13: Disposal considerations****· 13.1 Waste treatment methods**

- Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

· Uncleaned packaging:

- Recommendation: Disposal must be made according to official regulations. Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

- Recommended cleansing agents: Alcohol

**SECTION 14: Transport information****· 14.1 UN number or ID number**

- ADR, IMDG, IATA UN3295

**· 14.2 UN proper shipping name**

- ADR 3295 HYDROCARBONS, LIQUID, N.O.S. (Solvent naphtha (petroleum), light arom.), ENVIRONMENTALLY HAZARDOUS
- IMDG HYDROCARBONS, LIQUID, N.O.S. (Solvent naphtha (petroleum), light arom.), MARINE POLLUTANT
- IATA HYDROCARBONS, LIQUID, N.O.S. (Solvent naphtha (petroleum), light arom.)

**· 14.3 Transport hazard class(es)**· ADR

- Class 3 (F1) Flammable liquids.
- Label 3

· IMDG

- Class 3 Flammable liquids.
- Label 3

· IATA

- Class 3 Flammable liquids.

(Contd. on page 11)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.08.2023

Version number 3 (replaces version 2)

Revision: 23.08.2023

**Trade name: Stone Sealer - satin finish**

(Contd. of page 10)

· Label	3
· <b>14.4 Packing group</b> · ADR, IMDG, IATA	III
· <b>14.5 Environmental hazards:</b> · Marine pollutant: · Special marking (ADR):	Product contains environmentally hazardous substances: Symbol (fish and tree) Symbol (fish and tree)
· <b>14.6 Special precautions for user</b> · Hazard identification number (Kemler code): · EMS Number: · Stowage Category	Warning: Flammable liquids. 30 F-E,S-D A
· <b>14.7 Maritime transport in bulk according to IMO instruments</b>	Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category · Tunnel restriction code	3 D/E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3295 HYDROCARBONS, LIQUID, N.O.S. (SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.), 3, III, ENVIRONMENTALLY HAZARDOUS

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category E2 Hazardous to the Aquatic Environment  
P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

97-88-1 | n-butyl methacrylate

(Contd. on page 12)

EU

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 23.08.2023

Version number 3 (replaces version 2)

Revision: 23.08.2023

**Trade name: Stone Sealer - satin finish**

(Contd. of page 11)

· REGULATION (EU) 2019/1148· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· National regulations:

· Information about limitation of use: Employment restrictions concerning juveniles must be observed.  
Employment restrictions concerning pregnant and lactating women must be observed.

· Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

· Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· VOC EU 726.8 g/l

· **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

**SECTION 16: Other information**

This Safety Data Sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Laboratory· Date of previous version: 08.12.2022· Version number of previous version: 2

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
ICAO: International Civil Aviation Organisation  
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
DNEL: Derived No-Effect Level (REACH)  
PNEC: Predicted No-Effect Concentration (REACH)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
SVHC: Substances of Very High Concern  
vPvB: very Persistent and very Bioaccumulative  
Flam. Liq. 2: Flammable liquids – Category 2  
Flam. Liq. 3: Flammable liquids – Category 3  
Skin Irrit. 2: Skin corrosion/irritation – Category 2  
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
Skin Sens. 1: Skin sensitisation – Category 1  
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
Asp. Tox. 1: Aspiration hazard – Category 1  
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2